

# CRIOGENICI

| DN    | Ø INTERNO / INSIDE Ø | Ø ESTERNO / OUTSIDE Ø | ESERCIZIO (20°C)<br>SERVICE (68°F) | SCOPPIO (20°C)<br>BURST (68°F) | RAGGIO MIN.CURV<br>MIN. BEND RADIUS | PESI / WEIGHTS |
|-------|----------------------|-----------------------|------------------------------------|--------------------------------|-------------------------------------|----------------|
|       | (mm)                 | (mm)                  | (bar)                              | (bar)                          | (mm)                                | (gr/mt)        |
| 1/4   | 6,5                  | 11,5                  | 365                                | 1100                           | 35                                  | 230            |
| 13/32 | 11                   | 16,6                  | 285                                | 850                            | 60                                  | 400            |
| 1/2   | 13                   | 18,5                  | 265                                | 800                            | 70                                  | 460            |

| MATERIALI PER RACCORDI<br>MATERIAL FOR FITTINGS |                     |
|-------------------------------------------------|---------------------|
| X 8 Cr Ni 18 12                                 | UNI 6901 (AISI 305) |
| X 5 Cr Ni 18 10                                 | UNI 6901 (AISI 304) |
| X 5 Cr Ni Mo 17 12                              | UNI 6901 (AISI 316) |
| X 6 Cr Ni Ti 18 11                              | UNI 6901 (AISI 321) |
| P. Cu Zn 40 Pb 2                                | UNI 5705-65 (OT 58) |
| P. Cu Zn 40                                     | UNI 4891 (OT 60)    |